

Glulam Product Information

Product Description

Glulam beams are produced by gluing laminates of timber together under pressure and heat.

As the raw material is precisely planed the resulting product is not only strong and stable but also aesthetically pleasing. This give it significant advantages over other structural materials.

Our Glulam beams are:

- Available in four grades (GL24, GL28, GL32, GL36)
- Manufactured from Spruce in accordance with EN 386 / EN 14080
- Graded in accordance with EN 14081 or DIN 4074-4
- Surfaced on four sides and chamfered

Other engineered products including CLT (cross laminated timber), Duo/trio Laminated timber and KVH construction timber.

GLULAM GL24H INDUSTRIAL SPRUCE GLULAM

NOMINAL SIZE (MM)	ACTUAL SIZE (MM)	PIECES PER PACK	LENGTHS AVAILABLE (M)
45	220	48	12
45	220	40	
45	240	40	
45	253	32	
45	300	32	
45	304	33	

GLULAM GL28C VISUAL QUALITY SPRUCE GLULAM

NOMINAL SIZE (MM)	ACTUAL SIZE (MM)	PIECES PER PACK	LENGTHS AVAILABLE (M)
90	180	n/a	12
90	225	n/a	
90	240	n/a	
90	253	n/a	
90	270	n/a	
90	315	n/a	
90	360	n/a	
90	405	n/a	
90	450	n/a	

Glulam Product Information

GLULAM GL28C VISUAL QUALITY SPRUCE GLULAM

NOMINAL SIZE (MM)	ACTUAL SIZE (MM)	PIECES PER PACK	LENGTHS AVAILABLE (M)
90	495	n/a	12
115	270	n/a	
115	360	n/a	
120	360	n/a	
140	140	n/a	
140	180	n/a	
140	200	n/a	
140	225	n/a	
140	240	n/a	
140	253	n/a	
140	270	n/a	
140	315	n/a	
140	360	n/a	
140	405	n/a	
140	450	n/a	
140	495	n/a	